

LOVOL



EU Stage V



Rated Power	10.9kW/2400rpm
Operating Weight	1810kg
Bucket Capacity	0.04m ³

FR18E2-u

MINI EXCAVATOR

TECHNICAL SPECIFICATIONS



Dimensions

Shipping Length	3575mm
Shipping Ground Length	1230mm
Shipping Height	2347mm
Shipping Width	990mm
Cab Height	2347mm
Ground Clearance of Counter weight	438mm
Min. Ground Clearance	150mm
Tail Turning Radius	640mm
Wheel Tread	1230mm
Track Length	1593mm
Track Gauge	760/1050mm
Track Shoe Width	230mm



Working Range

Max. Digging Height	3540mm
Max. Dumping Height	2440mm
Max. Digging Depth	2310mm
Max. Vertical Digging Depth	1910mm
Max. Digging Radius	3905mm
Max. Ground Digging Radius	3845mm
Min. Turning Radius	1443mm
Dozer Blade Lifting Height	260mm
Dozer Blade Falling Height	180mm



Engine

Engine Model	YANMAR 3TNV70-PFN
Number of Cylinders	3
Max. Torque/Speed	48-52.3/1800±50N·m/rpm
Displacement	0.854L



Main Performance

Bucket Digging Force	15.2kN
Arm Digging Force	8.5kN
Max. Traction Force	13.5kN
Max. Walking Speed	3.7km/h
Min. Walking Speed	1.9km/h
Rotary Speed	9r/min
Gradeability	30°
Ground Pressure	29kPa



Hydraulic system

Max. Main Pump Flow	45L/min
Main Safety Valve Pressure	21.6MPa



Other Specifications

Boom Length	1828mm
Arm Length	950mm
Track Section Number (each side)	37
Track Roller Number	3



Refill Capacity

Fuel Tank	19L
Hydraulic Tank	15.4L
Engine Oil	3.7L

LOVOL HEAVY INDUSTRY GROUP CO.,LTD.

Address: No. 75, Huanghe East Road, Huangdao District, Qingdao City, Shandong Province, China.

Website: en.wlovol.com

E-mail: zhangkuisheng@lovol.com

TEL: +86-17685707806

Facebook: LOVOL HEAVY INDUSTRY

As manufacturer, LOVOL has right to constantly upgrade and improve our products without informing to customers. The pictures in literatures are for reference only, the detailed specifications are subject to real products.