



Engine	WEICHAI LOVOL
Engine Mark	WEICHAI LOVOL
Rated Power	74kW / 71.9kW
Operation Weight (Standard Arm)	7900kg / 8020kg
Operation Weight (Telescopic Arm)	8500kg / 8600kg

Model
FLB468-II
SIDE-SHIFT BACKHOE LOADER
Emission III standard engine

FLB468-II Backhoe Loader Specifications

Specification	Standard		Optional	
Engine				
Engine	WEICHAI LOVOL			
Engine Mark	WEICHAI LOVOL			
Model	WP4.1G100E311	WP4.1G100E441		
Engine Type	Diesel Engine, 4 Stroke, Inline, Direct Injection, Water Cooled, Turbocharger			
Number of Cylinder-Bore×Stroke	4-105×118mm			
Rated Engine Power / Speed (ISO)	74kW / 2200rpm	71.9kW / 2200rpm		
Engine Torque / Speed	395N·m / 1400-1600rpm	420N·m / 1600rpm		
Displacement	4.088L	4.087L		
Air Filter	Dry Air Filter			
Fuel Tank Capacity	130L	142L	152L	
<ul style="list-style-type: none">• The engine meets EU Stage III emission standard• Auto idle system and auto stop system• Intercooler (optional configuration)• Engine oil cooler (optional configuration)• Electrical fuel supply (optional configuration)				

Transmission System

Type	Four Wheel Drive			
Front Axle Oscillation Angle	22°			
Transmission	Torque Converter			
Gear Shift	Power shift, synchro shuttle, 4 forward, 4 reverse		Power shuttle transmission, 4 forward, 4 reverse	
Max. Travel Speed	37km/h	40km/h	37km/h	40km/h
Front Tyre Size	14-17.5	12.5×18	14-17.5	12.5×18
Rear Type Size	19.5L-24	16.9×28	19.5L-24	16.9×28
Traction Force	70kN			
<ul style="list-style-type: none">• The transmission adopts WEICHAI LOVOL, it is durable and reliable.• Four wheel drive system, available with either four wheel drive (4WD) or two wheel drive (2WD).• The differential lock operated on rear axle				

Steering System

Type	Hydrostatic Power Steering			
Outside Front Wheels Turning Circle (A)	7.50m (with braked) / 8.86m (without braked)			
Outside Loader Bucket Turning Circle (B)	10.90m (with braked) / 11.60m (without braked)			

Brake System

Service Brake	Wet Type-Power Braking			
Parking Brake	Hand Brake			

Hydraulic System

Hydraulic System	Open Center			Closed Center	
Hydraulic Pump	Gear Pump			Variable Flow Axial Piston Pump	
Hydraulic Flow	145L/min	150L/min	154L/min	135L/min	150L/min
Hydraulic Pressure	225Bar	245Bar	250Bar	250Bar	250Bar
Hydraulic Oil Capacity	130L	138L		152L	

- Hydraulic oil cooler (optional configuration)

Standard Equipment

- Rops canopy steel cab - compliant ROPS/FOPS, safe work, air condition
- Adjustable seat with safety belt suitable for various position working conditions
- Front & side instrument panel (hour meter, voltage charger, water-cooling temperature, engine oil pressure, fuel level, etc.), working light, front & rear wipers, horn, backup alarm

Optional Equipment

- Intercooler
- Hydraulic auger
- Automatic belt tensioner
- Flail head
- Hydraulic breaker
- GPS system

LOVOL HEAVY INDUSTRY GROUP CO.,LTD.

Address: No.75, Huanghe East Road, Huangdao District, Qingdao City, Shandong Province, China.

<https://en.wlovol.com/>

As manufacturer, LOVOL has right to constantly upgrade and improve our products without informing to customers. The pictures in illustrators are for reference only, the detailed specifications are subject to real products.

Specification	Standard			Optional			
Working Device							
Height to Top of Cab (C)	2700mm			2850mm		2890mm	
Wheelbase (D)	2170mm			2200mm		2250mm	
Overall Length (E)	5850mm			5900mm		5950mm	
Overall Height (F)	3500mm			3600mm		3820mm	
Loading Bucket Type	General Purpose Bucket		Multi Pupose Bucket (4 in 1)		Multi Pupose Bucket (6 in 1)		
Loading Bucket Capacity	1.0m³ (SAE Heaped)		1.15m³ (SAE Heaped)				
Loading Bucket Width	2200 mm		2300 mm		2350 mm		
Rated Load	1700kg		3050kg		3480kg		
Bucket Breakout Force	28kN		58kN		61kN		
Arm Breakout Force	37kN		58kN				
Dump Angle	43°		45°		47°		
Loader Lifting Height (G)	4100mm		4300mm				
Hinge Pin Height (H)	3400mm		3500mm		3600mm		
Dumping Height (I)	2600mm		2800mm		2900mm		
Fully Dump Reach at Full Height (J)	780mm		800mm				
Loader Digging Depth (K)	70mm		95mm		110mm		
Rollback Angle at Ground Level	45°		47°				
Digging Bucket Type	Standard Profile Bucket						
Digging Bucket Capacity	0.18m³ SAE Heaped		0.20m³ SAE Heaped				
Digging Bucket Width	610mm		650mm		700mm		
Bucket Digging Force	45kN		58kN		63.5kN		
Arm Digging Force	44kN		55kN		63kN		
Swing Arc	180°						
Bucket Rotation Angle	180°		204°				
Side Shift	1010mm						
Digging Arm Type	Standard Arm			Telescopic Arm			
				Ret	Ext		
Max. Digging Radius (L)	5300mm	5450mm	5700mm	5350mm	6400mm	6700mm	6900mm
Max. Loading Height (M)	3500mm	3600mm	3900mm	3350mm	4250mm	4400mm	4500mm
Max. Digging Height (N)	5100mm	5200mm	5500mm	5000mm	5900mm	6200mm	6600mm
Max. Digging Depth (O)	4000mm	4100mm	4300mm	4020mm	4600mm	5200mm	5810mm

Electrical System

Electric system	12V					
Battery	12V 100Ah					
Alternator	65A			150A		

